

**SPINDLE MOUNTED TELEMETRY SYSTEM**CROSS REFERENCE TO RELATED APPLICATION

The present application is based on and claims the benefit of U.S. provisional patent applications  
5 Serial No. 60/271,875, filed February 27, 2001 and  
Serial No. 60/352,755, filed January 28, 2002, the  
contents of which are hereby incorporated by  
reference in their entireties.

BACKGROUND OF THE INVENTION

10 The present invention relates to a transducer  
mounted to a spindle. More particularly, the present  
invention relates to a telemetry system that  
transmits signals from the rotating transducer to a  
stationary body.

15 A common system for transmitting signals from a  
rotating transducer to a stationary member is by  
using a contacting slip ring. In vehicle spindle  
mounted applications, the slip ring, as well as an  
optional angular encoder, require an anti-rotate  
20 connection to a non-spinning portion of the vehicle.  
Most slip rings also require that the slip ring  
tracks and brushes be located on a small radius  
around the axis of rotation for the purposes of  
decreasing the surface speed of the brushes in the  
25 slip ring assembly. Typically, this requires that the  
slip ring assembly be placed outboard of the vehicle  
wheel assembly on the axis of rotation. The anti-  
rotate connection wraps around the outside of the  
wheel assembly to attach on the inside of the wheel

2024230 6668001

at the suspension such that the antirotate is attached to a non-rotating portion of the vehicle that follows the wheel steering and bounce so as to avoid relative motion of the vehicle mounting location and the slip ring mounting at the spindle. Accordingly, the slip ring assembly thus projects outwardly from the wheel, which is undesirable since the projection may contact obstacles. In many jurisdictions, local street laws may prohibit driving on public roads with such a projection.

As an alternative to a slip ring, telemetry allows signals from a rotating body to be transmitted wirelessly to a stationary body. Telemetry can have some advantages over slip rings in that it does not rely on a brush contact to transmit the signal. Although telemetry has been incorporated into other vehicle spindle applications, such systems have had many separate components and which are positioned on the rotating and non-rotating portions of the vehicle spindle. In these other assemblies, the spindle bearings provide the means or positioning for components rotating relative to each other. This design may require electrical components to be potted into custom rims. The custom rims are expensive and require alignment of a stationary pick-up device during installation. In addition, the runout of a rim and/or spindle bearings, and/or deformation of the rim under loading can create problems and interferences between the rotating rim components,

and the stationary suspension or vehicle mounted components due to varying gap between the stationary body and the rotating body.

In another telemetry system, the telemetry assembly is comprised of a rotor and stator portion, which must be placed on the axis of rotation to maintain low bearing and/or seal speeds and use of standard off the shelf encoder products. Due to the existing vehicle spindle geometry, which occupies the space at the axis of rotation, the telemetry assembly must be placed outboard of the wheel on the axis of rotation. An anti-rotate device must again wrap around the wheel to an attachment point behind the wheel, thereby having the disadvantages discussed above with the slip ring assembly. In addition, these systems are not easily adapted to other wheels or environments.

Accordingly, there is an on-going need to improve telemetry systems in rotating applications such as vehicle spindle or helicopter spindle blade applications. A telemetry system that addresses one or more of these problems would be a valuable design improvement to the current state of the technology.

#### SUMMARY OF THE INVENTION

The present invention relates to a telemetry assembly for a spindle. The telemetry assembly includes a wireless transmitter coupled to the spindle to rotate therewith and a receiving antenna wirelessly coupled to the transmitter. A guiding

system is coupled to the wireless transmitter and the receiving antenna to guide rotation of the wireless transmitter relative to the receiving antenna.

In one embodiment, the telemetry assembly can be used in a telemetry system that includes a hub adapter mountable to the spindle and a transducer mountable to the hub adapter. Housings may be provided in order to support the wireless transmitter and the receiving antenna. The housings may be annular in design and include a central aperture so as to allow the telemetry assembly to be placed concentrically with the existing spindle bearings, thus allowing the location of the telemetry system to be maintained inboard of the wheel assembly wherein at least one of the spindle or a non-rotating member of the spindle extends through the central aperture and thus simplify the antirotate attachment and minimize the protrusion from the face of the spindle.

The telemetry assembly is easily mountable to various types of spindles. A stator housing of the telemetry assembly is mountable to a non-rotating element of the spindle. An antirotate connection assembly secures the stator housing to the non-rotating element. The stator housing can be disposed between the connection assembly and a rotor housing.

The guiding system provides for independent control of the position and rotation of the rotor relative to the stator, thus eliminating the dependency on spindle bearing accuracy, and/or manual

1008393 0330

alignment of other separate telemetry components such as electronic-embedded rims and stationary receivers, to maintain the relative positions of the rotor and stator portions of the telemetry system. A central  
5 aperture is provided in the guiding system to allow the spindle or rotating members coupled to the spindle to extend therethrough.

The housings provide a compact, modular, self-guided assembly that is easily mountable to various  
10 types of spindles. In particular, the housings are particularly useful in mounting to various vehicles, including different types of automobiles. If desired, an angular positioning device and a wireless power coupling can be used with or incorporated within the  
15 telemetry system.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a sectional view of a wheel assembly of a vehicle spindle.

FIG. 2 is an exploded perspective view of the  
20 telemetry and wheel assembly.

FIG. 3 is a schematic block diagram of a telemetry system.

FIG. 4 is a top plan view of a first portion from inside the telemetry assembly.

25 FIG. 5 is a top plan view of a second portion from inside the telemetry assembly.

FIG. 6 is a sectional view of the telemetry assembly taken along line 6--6 of FIG. 5.

202220" 6666800T

FIGS. 7-9 are sectional views of the telemetry assembly taken along lines 7--7, 8--8 and 9--9 of FIG. 4, respectively.

FIG. 10 is a partial sectional view of an alternative telemetry assembly.

FIG. 11 is a schematic view of an alternative telemetry assembly.

FIG. 12 is a schematic view of an alternative telemetry assembly.

10 DETAILED DESCRIPTION OF THE ILLUSTRATIVE EMBODIMENTS

Referring to FIG. 1, a telemetry system 10 includes a telemetry assembly 18 and transducer 20 that are mountable to a hub 12 of a spindle 14 (herein by example a vehicle spindle). Spindle 14 has a spindle axis 15 about which rotating elements rotate relative to non-rotating elements. Hub 12 is connected to a shaft 16 that rotates on vehicle spindle bearings 17, schematically illustrated. Generally, the telemetry system 10 includes the telemetry assembly 18 and optional hub electronics 19. The telemetry assembly 18 is couplable to a transducer 20 (herein a force transducer) that measures forces and loads upon the vehicle spindle 14, although other forms of transducers such as displacement, acceleration, temperature and pressure transducers mounted to the vehicle spindle 14 can also be used. The telemetry assembly 18 can be disposed on a side 20A of the transducer 20 facing

20220668007

the hub 12 to form a compact system with minimal projection from the vehicle spindle.

Referring also to FIG. 2, transducer 20 is coupled to hub 12 of the vehicle spindle 14. In the embodiment illustrated, a hub adapter 22 is secured to the hub 12, while the transducer 20 is secured to the hub adapter 22. In some applications, a hub adapter 22 may not be necessary. The hub adapter 22 allows the transducer 20 to be easily used on many types of hubs 12. Fasteners 23 secure the hub 12 to the hub adapter 22, while fasteners 24 secure the transducer 20 to the hub adapter 22. In the embodiment illustrated, the transducer can comprise a force and moment transducer wherein an outer rim 26 of the transducer 20 is secured to a wheel rim 28 supporting a tire not shown. This type of transducer is described in U.S. Pat. 5,969,268, which is hereby incorporated by reference in its entirety, although other forms of transducers can benefit from the telemetry system 10 or telemetry assembly 18 herein described.

Generally, the transducer 20 has a first side 20A facing the hub 12 and a second side 20B facing in an opposite direction away from the hub 12. The telemetry system 10 includes hub electronics 19 coupled to the transducer 20 to rotate therewith. Hub electronics 19 includes circuitry (digitization, telemetry conversion, signal conditioning and/or amplification to name a few) that is disposed on the

20220706 09:00:00

second side 20B of the transducer facing away from the hub 12. Due to the annular design of the telemetry system 10, the telemetry assembly 18, can be positioned concentrically about the axis 15 with the spindle bearings 17 and can be positioned on the first side 20A of the transducer 20, which faces the hub 12 and is coupled to hub adapter 22 via fasteners 29. One or more connectors 30 connect telemetry assembly 18 to circuits of hub electronics 19 and/or transducer 20. The telemetry assembly 18 can thus be disposed between the transducer 20 and elements of the spindle 14 such as a brake caliper 32. Location of the telemetry assembly 18 between transducer 20 and components of the spindle 14 forms a compact assembly, with benefits such as minimizing hanging mass on the spindle 14. Location of the hub electronics 19 on the other side 20B of the transducer 20 minimizes the heat seen by components forming the hub electronics 19, the heat being substantially generated by operation of the brakes to stop the vehicle. Meanwhile, less sensitive components of the telemetry system 10, and data and power transmitting components are located inwardly of the transducer 20 to form a compact assembly.

The telemetry assembly 18 includes central aperture 21 and two portions 34 and 36 that rotate relative to one another. Generally, the first portion 34 (or stator portion) is held substantially stationary with respect to the non-rotating portions



of the spindle or elements proximate thereto. As illustrated, the stator portion 34 and rotor portion 36 are rings that rotate relative to one another via a guiding system 72, discussed in detail below. By  
5 locating the telemetry assembly 18 as a ring about the axis of rotation on side 20A of the transducer 20, a large, cumbersome anti-rotate device disposed around the tire and wheel assembly is also not needed. Central aperture 21 allows portions of  
10 spindle 14 or rotating members coupled to the spindle 14 to extend therethrough. Although illustrated as rings or plate members facing each other, those skilled in the art will recognize that concentric rings or cylinders and other designs may be used for  
15 stator portion 34 and rotor portion 36. In the embodiment illustrated, rotor portion 36 is coupled to hub adapter 22 via fasteners 30 to rotate therewith. Although, if desired, the rotor portion 36 can also be coupled to the force transducer 20 or any  
20 other rotating element.

In the embodiment illustrated in FIG. 1, anti-rotate connection assembly 38 holds stator portion 34 substantially stationary (i.e. at least not rotating with rotor portion 36) with respect to a non-rotating  
25 portion of the spindle, such as spindle element 40. Connection assembly 38 can be attached to elements of vehicle spindle 14 or other non-rotating spindle elements which move with the hub 12 translationally and rotate in axes other than the spinning rotation,

10083930 000000

such as brake caliper 32 (FIG. 2) and allows  
telemetry assembly 18 to be spaced apart from rim 28.  
Connection assembly 38 includes an elongated member  
39 secured to spindle element 40 (which is non-  
5 rotating). As illustrated, connection assembly 38  
includes a ball 41 disposed in a ball receiver 42  
having a cavity 43 with sufficient clearance to allow  
the ball 41 to move relative to the cavity 43 to  
respond to various alignment positions of the  
10 antirotate assembly 38 relative to the telemetry  
assembly 18.

Generally, connection assembly 38 inhibits  
movement of stator portion 34 about spindle axis 15  
while allowing limited movement in the remaining  
15 linear and rotational displacements of a mutually  
orthogonal coordinate system having an axis  
coincident with spindle axis 15. If desired,  
elongated member 39 may be mounted to the stator  
portion 34 and the ball receiver 42 mounted to  
20 spindle element 40. The illustrated embodiment  
includes one connection assembly 38, wherein two ball  
receivers 42 are illustrated in FIG. 4 to allow for  
alternate positioning. Alternatively, one or more  
connection assemblies 38 may be used. In addition,  
25 other connection assemblies may be used such as one  
or more straps 27, for example. Since the telemetry  
assembly 18 includes central aperture 21 through  
which a portion of spindle 14 or elements connected  
thereto can extend, the connection assembly 38 can be

2025 RELEASE UNDER E.O. 14176

mounted inboard on side 20A of the transducer 20, or at a radial position from the axis 15 less than the maximum radial distance of a rotating element of the spindle 14, for example transducer 20 or rim 28.

5 Accordingly, rotation of elements coupled to spindle 14 can take place around connection assembly 38.

Referring to FIG. 2, signals indicative of forces sensed by transducer 20 are sent to telemetry assembly 18 and wirelessly transmitted from rotor portion 36 to stator portion 34. These signals are then transmitted to transducer interface 44 via connectors 45 and cables 46 for data collection. Shielding may be provided to protect connectors 45 and cables 46 from heat generated by a rotor of the wheel assembly. In a further embodiment, power is inductively transmitted from transducer interface 44 or other separate power supply to stator portion 34 via cables 46 and connectors 45. Power can then be transmitted to rotor portion 36 and provide power to the circuitry of hub electronics 19 and/or transducer 20. Alternatively, if desired, other power cells 53 such as batteries or solar cells can be mounted to rotate with the transducer 20 and wheel assembly to power some or all of these components.

25 FIG. 3 illustrates a block diagram of telemetry system 10. In the exemplary embodiment, sensors 47 sense forces that are amplified by amplifiers 48. From amplifiers 48, signals are sent to data transmitter (or wireless transmitter) 49, which is

coupled to rotor portion 36. Data transmitter 49 wirelessly transmits data through data coupling 50 to data receiver (or receiving antenna) 51, which is coupled to stator portion 34. Data receiver 51 is a ring or arced assembly about spindle axis 15. Data transmitter 49 and data receiver 51 are spaced apart from each other. Data transmitter 49 generally travels in a circular path spaced apart from and opposed to data receiver 51. Transmitted signals can be analog, digital or any combination thereof. In one embodiment illustrated, each channel is sampled at 20,000 samples per sec, and wherein eight channels of data are multiplexed for transmission. After receipt by the data receiver 51, the digital signals can be used as digital data or converted to analog signals, as desired. The signals are provided to a recorder or data acquisition system through transducer interface 44. In one embodiment, transducer interface 44 includes a separate board (daughter board) for each spindle, the separate board being coupled to a mother board.

Transducer interface 44 or other power supply can also provide power to power driver 52. Power driver 52 transmits power through power coupling 54 to power regulator 56. In one embodiment, power coupling 54 is an inductive coupling wherein power driver 52 and power regulator 56 are spaced apart from each other and are couplable to each other in order to transfer electrical power. In a further

embodiment, power driver 52 and power regulator 56 are coils that each form an annular ring about the spindle axis 15.

Typically, there is a need to know the angular position of transducer 20 as it rotates with the hub 12. If desired, telemetry assembly 18 can include sensor 58 operably coupled to the stator portion 34 and rotor portion 36 to sense the angular position of rotor portion 36 relative to stator portion 34. Generally, sensor 58 can be a resolver or an incremental or absolute encoder. The sensor 58 generally operates under optical, magnetic, resistive, capacitive, hall-effect, or other techniques.

FIGS. 4-6 illustrate different views of components of telemetry assembly 18. FIG. 4 illustrates a view of stator 34 from inside telemetry assembly 18. As illustrated, stator portion 34 includes stator housing 60 that is an annular ring including ball receivers 42 that couple to anti-rotate connection assemblies, such as connection assembly 38 illustrated in FIG. 1. In particular, ball receivers 42 include cavities 43 for receiving balls 41 (FIG. 1). The width of the cavities 43 corresponds to the diameter of the balls 41 in order to inhibit rotation of the stator portion 36, while the radial length (from axis 15) and the depth (FIG. 1) allow movement of the ball 41 in each of the cavities 43.

In the embodiment illustrated, data receiver 51 is an arced assembly positioned on stator housing 60. Power driver 52 is an annular ring that is also positioned on stator housing 60. Sensor 58 is also  
5 illustrated and includes one or more optical sensing devices 62 and encoder circuitry 64. Optical sensing devices 62 sense the position of rotor portion 36 and provide an output signal indicative thereof. The optical sensing device or devices 62 senses a  
10 reference position on the rotor, possibly through quadrature feedback signals and indexing as in known in the art. The use of quadrature output signals allows the direction of rotation of rotor portion 36 to be determined. In one embodiment, two of the  
15 optical sensing devices 62 provide square wave periodic signals substantially in quadrature (defined by a phase shift of  $90^\circ$ ) indicative of direction. The encoder 64 interprets rotational position data provided by the optical sensing devices 62 and sends  
20 the corresponding signals to transducer interface 44.

With reference also to FIG. 6, a side view of one possible optical sensing device 62 is shown. Optical sensing device or devices 62 are configured to sense the presence of indications on a disk 65,  
25 which is coupled to rotor portion 36 with fasteners 66 to rotate therewith.

FIG. 5 illustrates a view of rotor portion 36 from inside telemetry assembly 18. As illustrated, rotor portion 36 includes rotor housing 68. Data

transmitter 49 and power regulator 56 are both annular rings positioned on rotor housing 68.

204220" 666600T  
5 With reference also to FIGS. 6-9, guiding system 72 is shown. Generally, guiding system 72 maintains alignment of stator portion 34 and rotor portion 36 during relative rotation thereof. In particular, guiding system 72 maintains a substantially constant gap between data transmitter 49 and data receiver 51. A substantially constant gap between power driver 52  
10 and power regulator 56 is also maintained. The position of the encoder components is also maintained. The gaps allow proper transmission of data and power through data coupling 50 and power coupling 54, and angular sensing. It is understood  
15 that an annular self guided assembly as this may include any single or combination of functions described above, as desired for various applications.

Referring to the embodiment illustrated in FIG. 7, guiding system 72 can include bearing pad housing  
20 73, bearing pads 74 and a cylindrical bearing race 76 that includes a guided groove that couples to bearing pads 74. Bearing pads 74 are equally spaced apart about spindle axis 15. Bearing pads 74 are secured to bearing pad housing 73 with fasteners 77. Bearing pad  
25 housing is secured to stator portion 34 with fasteners 78. Although illustrated as a plurality of bearing pads 74, a single bearing pad or ring may also be used. Bearing race 76 is secured to rotor portion 36 with fasteners 79. Similarly, the location

of the bearing pads 74 could be moved to the rotating side, and the groove to the non-rotating side of the telemetry assembly 12 in a location similar to pad housing 73 Suitable materials for bearing pads 74 and bearing race 76 include aluminum, hard-coated materials, stainless steel and various other types of metallic, nonmetallic, intermetallic, ceramic, composite, metal filled or backed plastics, lubricant filled self lubricating materials, thermoset plastic, thermoplastic or other similar materials, or combinations thereof. Examples of hard-coated materials include hard-coated aluminum, hard anodize aluminum material, nickel plated material and chrome plated material. Further, the materials for pad 74 and race 76 can include bearing grade polymers, engineering plastics, synthetic resin materials, polyimide resins, polymerethane, PEEK (polyaryletheretherketone), phenolic and various compositions of these with fillers such as graphite or Teflon®, for example graphite filled polyimides such as Duratron® and Vespel®. Various combinations of these materials may be applied to provide an adequate bearing. For example, pad 74 may be made of stainless steel while a groove in race 76 is made of PEEK. Alternatively, a PEEK pad may be disposed in a stainless steel groove. Although the guiding system 72 described above is particularly advantageous due to its ability to handle heat and corrosive environments, guiding system 72 can be any rotational



guiding system including ball bearings, air bearings, magnetic levitation, etc.

Seals 80 inhibit contaminants from the bearing pad 74 and bearing race 76 coupling. Spacer 82 is provided to space one of the seals 80 from bearing pad 74. Seals 80 can be leather, plastic, Teflon®, rubber, wool, felt, polypropylene felt, synthetic or material for example formed from aramid such as Conex® felt, Nomex® felt and other materials, and/or combinations thereof. A flange 84, coupled to the bearing race 76 via fasteners 86, further shields contaminants from entering the guiding system 72 by producing a labyrinth, and reduces a gap between stator housing 60 and rotor housing 68 proximate the guiding system 72.

Stator housing 60 and rotor housing 68 face each other to form a cavity 88. Data transmitter 49, data receiver 51, power driver 52, power regulator 56, sensor 58, optical sensing devices 62, encoder 64 and other elements can be disposed in cavity 88. If desired, additional seals may be used to prevent unwanted entry of dirt, oil and other contaminants from entering between stator housing 60 and rotor housing 68 into cavity 88.

FIG. 7 is a cross section that shows a wire coupling 90 between connector 45 and power coupling 52. In addition, FIG. 8 illustrates a wire coupling 92 between connector 45 and data receiver 51. In FIG. 9, a wire coupling 94 is illustrated between

10083939-022702

connector 30 and components of rotor portion 36, namely data transmitter 49 and power regulator 56. Connector 30 is used to couple rotor portion 36 to hub electronics 19 and transducer 20. A wire coupling  
5 96 between connector or connectors 45 and encoder sensor 64 is also shown.

Referring to FIG. 10, an alternative embodiment of a portion of a housing 140 including a rotor housing (or plate) 142 and a stator housing (or  
10 plate) 144 is illustrated. Like the embodiment described above, the rotor housing 142 is rotatable about the axis of rotation and relative to the stator housing 144. The rotor housing 142 is coupled to rotate with the transducer 20. The rotor housing 142  
15 can be secured to the transducer 20 or to the hub adapter 22. A wireless coupling is provided between the rotor housing 142 and the stator housing 144. The wireless coupling allows signals from transmitter 146 to be received by the receiving antenna 148, and then  
20 transmitted to onboard data collection circuitry provided on the vehicle. A power coupling is also provided between the rotor housing 142 and the stator housing 144. The power coupling provides electrical power to the circuitry of the transducer 20,  
25 transmitter 146 and/or circuitry of hub electronics 19.

The housing 140 is self-supporting and includes a bearing assembly or guiding system 150, herein a duplex pair of angular contacting ball bearings, that

2025 RELEASE UNDER E.O. 14176

supports the rotor housing 142 relative to the stator housing 144 and allows rotation thereof. In another embodiment, a single pair of radial contact bearing or four point contact bearing may be used. The power  
5 coupling is an inductive coupling and is formed between spaced apart coils 194 and 196 that are couplable to each other in order to transfer electrical power. The coils 194 and 196, like the  
10 embodiment described above, each form an annular ring about the axis of rotation and are potted in each respective housing so as to be protected from water, dirt and other contaminants.

The ring housing 140 includes an encoder 156 or other similar angular position sensing device  
15 operably coupled to the rotor housing 142 and the stator housing 144. In the embodiment illustrated, the encoder 156 comprises an incremental Hall effect device having a ring gear 160 with projecting teeth (including an index tooth) and Hall effect sensors  
20 162 and a magnet 164. In the embodiment illustrated, the ring gear 160 is coupled to the rotor housing 142 to rotate therewith, while the magnet 164 and Hall effect sensors 162 are coupled to the stator housing 144.

25 In a further embodiment, two ring gears are provided which are angularly positioned one-half tooth apart from each other in order to allow for quadrature measurements to be made, thereby increasing the effect of resolution of the encoder.

Other forms of encoders such as optical encoders can also be used.

20/220" 6E6E800T  
The receiving antenna 148 comprises a ring or arced assembly about the axis of rotation. The transmitting antenna 146 is spaced apart from the receiving antenna 148 and generally travels in a circular path equivalent to the receiving antenna 148. The transmitted signals can be analog, digital or a combination thereof. Annular seals are provided to seal an inner cavity 180 having the transmitting antenna 146, receiving antenna 148 and encoder 156 protected from the outside environment and bearing grease from the bearing assembly 150. In the embodiment illustrated, a first annular seal 182 is provided between the stator housing 144 and an outer peripheral of the ring gear 160 of the encoder 156. A second annular seal 184 is provided between the stator housing 144 and a bearing support flange 186 of the rotor housing 142. A third annular seal 188 is provided between the rotor housing 144 and another bearing support flange 190. In the embodiment illustrated, the seals 182, 184 and 188 are spring loaded and comprise Teflon that contacts nickel, chrome or other similarly plated surfaces. Other sealing or excluding devices can be used including non-spring loaded seals, polymer seals, positive air pressure, and/or labyrinth seals could be used.

As appreciated by those skilled in the art, other telemetry assembly designs can be used. FIGS.

11 and 12 illustrate alternative embodiments of  
telemetry assemblies according to the present  
invention. In FIG. 11, telemetry assembly 200 is  
illustrated. Telemetry assembly 200 includes central  
5 aperture 201, first portion 202 and a second portion  
204. Second portion 204 rotates relative to first  
portion 202. Similar to the embodiments described  
above, first portion 202 and second portion 204 face  
each other to form a cavity 205 therebetween. Data is  
10 wirelessly transmitted from data transmitter 206 to  
data receiver 208. Data transmitter 206 and data  
receiver 208 are concentrically arranged. Likewise,  
power driver 210 and power regulator 212 are  
concentrically arranged and transmit power from first  
15 portion 202 to second portion 204.

FIG. 12 illustrates an embodiment of a telemetry  
assembly 220 including central aperture 221, a first  
portion 222 and a second portion 224, which rotates  
relative to first portion 222 in a cylindrical manner  
20 where first portion 222 has a diameter less than  
second portion 224 to form a cavity 225 therebetween.  
In other words, second portion 224 is concentrically  
arranged around first portion 222. In this  
embodiment, data can be transferred between data  
25 coupling elements 226 and 228 in the cavity.  
Likewise, power can be transferred between power  
coupling elements 230 and 232. Alternatively, first  
portion 222 can rotate relative to second portion  
224. Data and power are transferred between data

2025 RELEASE UNDER E.O. 14176

coupling units 226 and 228 and between power coupling units 230 and 232, respectively.

Generally, the elements forming the data and power couplings can be disposed at different radial distances from the axis of rotation (such as illustrated in FIGS. 11 and 12), or on opposite sides of a plane that is perpendicular to the axis of rotation (such as illustrated in FIG. 6), or a combination thereof. Likewise, the housings can be cylindrically arranged with a cavity formed therebetween, or as opposed discs on opposite sides of a plane that is perpendicular to the axis of rotation. In each of the above-described embodiments, a guiding system similar to that illustrated is provided to maintain alignment and spacing for each of the data and power couplings, thus maintaining a compact and modular telemetry assembly.

Although the present invention has been described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.

1008999.022702  
202209060001